MyMagento

Release 2.2.0

Adam Korn

Apr 07, 2024

README

1 MyMagento - Python Magento 2 REST API Wrapper **1**
- 1.1 About MyMagento . . . 1
  - 1.1.1 Main Components . . . 1
  - 1.1.2 Available Endpoints . . . 2
- 1.2 Installing MyMagento . . . 2
- 1.3 QuickStart: Login with MyMagento . . . 3
  - 1.3.1 Setting the Login Credentials . . . 3
  - 1.3.2 Getting a `Client` . . . 3
  - 1.3.3 Getting an `ACCESS_TOKEN` . . . 4

2 Interacting with the API **5**
- 2.1 Performing a `search()` . . . 5
- 2.2 Search Results: The `Model` Classes . . . 6
- 2.3 Building Custom Search Queries . . . 7
- 2.4 Making Authorized Requests . . . 7
  - 2.4.1 Example: Making a `get()` Request . . . 7

3 The `magento` Package **9**
- 3.1 The `clients` module . . . 9
- 3.2 The `search` module . . . 15
- 3.3 The `exceptions` module . . . 30
- 3.4 The `utils` module . . . 31

4 The `magento.models` subpackage **37**
- 4.1 The `model` module . . . 37
- 4.2 The `product` module . . . 41
- 4.3 The `category` module . . . 51
- 4.4 The `order` module . . . 53
- 4.5 The `invoice` module . . . 56
- 4.6 The `customer` module . . . 58

5 Get a Magento 2 REST API Token With MyMagento **61**
- 5.1 Setting the Login Credentials . . . 61
- 5.2 Getting a `Client` . . . 61
- 5.3 Setting Environment Variables . . . 62

6 Add discount on each product based on product price **63**
- 6.1 Solution Using MyMagento . . . 63

7 Changelog **65**
- 7.1 v2.1.0 . . . 65

8 Indices and tables 67

Python Module Index 69

Index 71

CHAPTER

ONE

MYMAGENTO - PYTHON MAGENTO 2 REST API WRAPPER

A Python package that wraps and extends the Magento 2 REST API

Explore the docs »

1.1 About MyMagento

What's MyMagento?

`MyMagento` is a highly interconnected package that wraps and extends the Magento 2 REST API, providing a more intuitive and user-friendly interface to access and update your store.

MyMagento simplifies interaction with the Magento 2 REST API

If you've worked with the Magento 2 API, you'll know that not all endpoints are created equally.

`MyMagento` aims to streamline your workflow by simplifying a variety of commonly needed API operations.

1.1.1 Main Components

The `Client`

- Handles all API interactions
- Supports multiple store views
- Provides access to all other package components

The `SearchQuery` and Subclasses

- `execute()` a search query on any endpoint
- Intuitive interface for *Building Custom Search Queries*
- All predefined methods retrieve data using only 1-2 API requests

The `Model` Subclasses

- Wrap all API responses in the package
- Provide additional endpoint-specific methods to retrieve and update data

1.1.2 Available Endpoints

`MyMagento` is compatible with every API endpoint

Endpoints are wrapped with a `Model` and `SearchQuery` subclass as follows:

Endpoint	Client Shortcut	`SearchQuery` Subclass	`Model` Subclass
orders	`Client.orders`	`OrderSearch`	`Order`
orders/items	`Client.order_items`	`OrderItemSearch`	`OrderItem`
invoices	`Client.invoices`	`InvoiceSearch`	`Invoice`
products	`Client.products`	`ProductSearch`	`Product`
products/attributes	`Client.product_attributes`	`ProductAttributeSearch`	`ProductAttribute`
categories	`Client.categories`	`CategorySearch`	`Category`
customers	`Client.customers`	`CustomerSearch`	`Customer`
endpoint	`Client.search('endpoint')`	`SearchQuery`	`APIResponse`

...

1.2 Installing MyMagento

To install using `pip`:

```
pip install my-magento
```

Please note that `MyMagento` requires `Python >= 3.10`

...

1.3 QuickStart: Login with MyMagento

`MyMagento` uses the `Client` class to handle all interactions with the API.

Tip: See *Get a Magento 2 REST API Token With MyMagento* for full details on generating an access token

1.3.1 Setting the Login Credentials

To generate an `ACCESS_TOKEN` you'll need to `authenticate()` your `USER_CREDENTIALS`.

Creating a `Client` requires a `domain`, `username`, and `password` at minimum.

```
>>> domain = 'website.com'
>>> username ='username'
>>> password = 'password'
```

If you're using a local installation of Magento you'll need to set `local=True`. Your domain should look like this:

```
>>> domain = '127.0.0.1/path/to/magento'
```

...

1.3.2 Getting a `Client`

Option 1: Initialize a `Client` Directly

```
from magento import Client

>>> api = Client(domain, username, password, **kwargs)
```

Option 2: Call `get_api()`

```
import magento

>>> api = magento.get_api(**kwargs)
```

`get_api()` takes the same keyword arguments as the `Client`

- If the `domain`, `username`, or `password` are missing, it will attempt to use the following environment variables:

```
import os

os.environ['MAGENTO_DOMAIN'] = domain
os.environ['MAGENTO_USERNAME']= username
os.environ['MAGENTO_PASSWORD']= password
```

...

1.3.3 Getting an ACCESS_TOKEN

Unless you specify `login=False`, the `Client` will automatically call `authenticate()` once initialized:

```
>> api.authenticate()

|[ MyMagento | website_username ]|:  Authenticating username on website.com...
|[ MyMagento | website_username ]|:  Logged in to username
```

CHAPTER

TWO

INTERACTING WITH THE API

Did you *Get a Magento 2 REST API Token With MyMagento*? Then let's start using the API!

2.1 Performing a search()

The `Client.search()` method lets you `execute()` a query on any API endpoint

It creates a `SearchQuery` for the endpoint, allowing you to retrieve data about

- An individual item (ex. `by_id()`)
- A list of items (ex. `by_list()`)
- Any search criteria you desire (see *Building Custom Search Queries*)

Example: search() an endpoint by_id()

```
# Query the "invoices" endpoint (also: api.invoices)
>>> api.search("invoices").by_id(1)

<Magento Invoice: "#000000001"> for <Magento Order: "#000000001" placed on 2022-11-01␣
↪03:27:33>
```

Example: search() an endpoint by_list()

```
# Retrieve invoices from a list of invoice ids
>>> ids = list(range(1,101))
>>> api.invoices.by_list("entity_id", ids)

[<Magento Invoice: "#000000001"> for <Magento Order: "#000000001" placed on 2022-11-01␣
↪03:27:33>, ...]
```

...

2.2 Search Results: The `Model` Classes

The `result` of any `SearchQuery` will be parsed and wrapped by a `Model` class in the `magento.models` subpackage.

These classes make the API response data easier to work with.

They also provide endpoint-specific methods to update store data and search for related items.

Example: Retrieving every `Order` containing a `Product`

Let's retrieve a `Product` using `by_sku()`

```
>>> product = api.products.by_sku("24-MB01")
```

We can search for orders containing this product in multiple ways:

```
# Using the Product itself
>>> product.get_orders()

[<Magento Order: "#000000003" placed on 2022-12-21 08:09:33>, ... ]

# Using an OrderSearch
>>> api.orders.by_product(product)
>>> api.orders.by_product_id(product.id)
>>> api.orders.by_sku(product.sku)

[<Magento Order: "#000000003" placed on 2022-12-21 08:09:33>, ... ]
```

Example: Retrieving all `Products` and `Invoices` for a `Category`

```
>>> category = api.categories.by_name("Watches")
>>> category.get_products()
>>> category.get_invoices()

[<Magento Product: 24-MG04>, <Magento Product: 24-MG01>, <Magento Product: 24-MG03>, ... ]
[<Magento Invoice: "#000000004"> for <Magento Order: "#000000004" placed on 2022-11-14␣
↪03:27:33>, ... ]
```

Example: Updating the Thumbnail `MediaEntry` of a `Product`

```
 # Update product thumbnail label on specific store view
>>> product.thumbnail.set_alt_text("bonjour", scope="FR")
>>> print(product.thumbnail)

 <MediaEntry 3417 for <Magento Product: 24-MB01>: bonjour>
```

...

Tip: Set the Store Scope

If you have multiple store views, a `store_code` can be specified when retrieving/updating data

- The `Client.scope` is used by default - simply change it to switch store `views`
- Passing the `scope` keyword argument to `Client.url_for()`, `Model.refresh()`, and some Model update methods will temporarily override the Client scope

---

...

2.3 Building Custom Search Queries

In addition to the predefined methods, you can also build your own queries

- Simply `add_criteria()`, `restrict_fields()`, and `execute()` the search
- The `since()` and `until()` methods allow you to further filter your query by date

---

Example: Retrieve Orders Over $50 Placed Since the Start of 2023

```
>>> api.orders.add_criteria(
...     field="grand_total",
...     value="50",
...     condition="gt"
... ).since("2023-01-01").execute()

[<Magento Order: "#000000012" placed on 2023-01-02 05:19:55>, ...]
```

...

2.4 Making Authorized Requests

The `Client` can be used to generate the `url_for()` any API endpoint, including a store `scope`.

You can use this URL to make an authorized `get()`, `post()`, `put()`, or `delete()` request.

2.4.1 Example: Making a `get()` Request

```
# Request the data for credit memo with id 7
>>> url = api.url_for('creditmemo/7')
>>> response = api.get(url)
>>> print(response.json())

{'adjustment': 1.5, 'adjustment_negative': 0, 'adjustment_positive': 1.5, 'base_adjustment':␣
↪1.5,  ... }
```

Note: A `search()` is simpler than making `get()` requests, as the result will be wrapped by `APIResponse` or other `Model`

```
# Retrieve credit memo with id 7 using a search
>>> memo = api.search("creditmemo").by_id(7)
>>> print(memo.data)
>>> print(memo)

{'adjustment': 1.5, 'adjustment_negative': 0, 'adjustment_positive': 1.5, 'base_adjustment':␣
↪1.5,  ... }
<magento.models.model.APIResponse object at 0x000001BA42FD0FD1>
```

CHAPTER

THREE

THE MAGENTO PACKAGE

The magento package provides various tools to help simplify interaction with the Magento 2 API.

magento.**get_api**(***kwargs*)

Initialize a Client using credentials stored in environment variables

Any valid Client kwargs can be used in addition to and/or instead of environment variables

Usage:

```
import magento

api = magento.get_api()
```

Parameters
kwargs – any valid kwargs for Client

Raises
ValueError – if login credentials are missing

Return type
Client

...

3.1 The clients module

class magento.clients.**Client**(*domain*, *username*, *password*, *scope=''*, *local=False*, *user_agent=None*, *token=None*, *log_level='INFO'*, *login=True*, ***kwargs*)

Bases: object

The class that handles all interaction with the API

__init__(*domain*, *username*, *password*, *scope=''*, *local=False*, *user_agent=None*, *token=None*, *log_level='INFO'*, *login=True*, ***kwargs*)

Initialize a Client

Important!

The Magento account you use to log in must be assigned a **User Role** that has the appropriate API resources included in its **Resource Access** settings

This can be verified in Magento Admin by going to:

```
System -> Permissions -> User Roles -> {Role} -> Role Resources -> Resource Access
```

and ensuring that `Sales`, `Catalog`, `Customers`, and any other desired resources are included

---

Parameters

- **domain** (`str`) – domain name of the Magento store (ex. `domain.com` or `127.0.0.1/magento24`)
- **username** (`str`) – username of the Magento Admin account
- **password** (`str`) – password of the Magento Admin account
- **scope** (`Optional[str]`) – the store view scope to `search()` and make requests on
- **local** (`bool`) – whether the Magento store is hosted locally
- **user_agent** (`Optional[str]`) – the user agent to use in requests
- **token** (`Optional[str]`) – an existing access token
- **log_level** (`str`) – the logging level for logging to stdout
- **login** (`bool`) – if `True`, calls `authenticate()` upon initialization
- **kwargs** – see below

...

Extra Keyword Arguments

- **log_file** (`str`) – log file to use for the client's `logger`
- **log_requests** (`bool`) - if `True`, the logs from `requests` will be added to the client's `log_file`

BASE_URL: str

The base API URL

USER_CREDENTIALS: Dict[str, str]

The user credentials

ACCESS_TOKEN: str

The API access token

domain: str

The Magento store domain

scope: str

The store view code to request/update data on

user_agent: str

The user agent to use in requests

logger: MagentoLogger

The `MagentoLogger` for the domain/username combination

store: Store

An initialized `Store` object

classmethod new()

Prompts for input to log in to the Magento API

Return type
Client

classmethod load(*pickle_bytes*)

Initialize a `Client` using a pickle bytestring from `to_pickle()`

Return type
Client

classmethod from_json(*json_str*)

Initialize a `Client` from a JSON string of settings

Return type
Client

classmethod from_dict(*d*)

Initialize a `Client` from a dictionary of settings

Return type
Client

url_for(*endpoint*, *scope=None*)

Returns the appropriate request url for the given API endpoint and store scope

Example

```
# Generate the url for credit memo with id 7
>> api=Client("domain.com", "user", "password")
>> api.url_for('creditmemo/7')
"https://domain.com/rest/V1/creditmemo/7"

# Generate the same url on the "en" store view
>> api.url_for('creditmemo/7', scope='en')
"https://domain.com/rest/en/V1/creditmemo/7"
```

Parameters

- **endpoint** (`str`) – the API endpoint
- **scope** (`Optional[str]`) – the scope to generate the url for; uses the `Client.scope` if not provided

Return type
str

search(*endpoint*)

Initializes and returns a `SearchQuery` corresponding to the specified endpoint

Note: Several endpoints have predefined `SearchQuery` and `Model` subclasses

If a subclass hasn't been defined for the `endpoint` yet, a general `SearchQuery` will be returned, which wraps the `result` with `APIResponse`

Parameters
endpoint (str) – a valid Magento API search endpoint

Return type
SearchQuery

property orders: OrderSearch
Initializes an OrderSearch

property order_items: OrderItemSearch
Initializes an OrderItemSearch

property invoices: InvoiceSearch
Initializes an InvoiceSearch

property categories: CategorySearch
Initializes a CategorySearch

property products: ProductSearch
Initializes a ProductSearch

property product_attributes: ProductAttributeSearch
Initializes a ProductAttributeSearch

property customers: CustomerSearch
Initializes a CustomerSearch

get(*url*)
Sends an authorized GET request

Parameters
url (str) – the URL to make the request on

Return type
Response

post(*url*, *payload*)
Sends an authorized POST request

Parameters

- **url** (str) – the URL to make the request on
- **payload** (dict) – the JSON payload for the request

Return type
Response

put(*url*, *payload*)
Sends an authorized PUT request

Parameters

- **url** (str) – the URL to make the request on
- **payload** (dict) – the JSON payload for the request

Return type
Response

delete(*url*)

Sends an authorized DELETE request

Parameters
url (str) – the URL to make the request on

Return type
Response

authenticate()

Authenticates the USER_CREDENTIALS and retrieves an access token

Return type
bool

validate()

Validates the token by sending an authorized request to a standard API endpoint

Raises
AuthenticationError if the token is invalid

Return type
bool

request(*method*, *url*, *payload=None*)

Sends an authorized API request. Used for all internal requests

Tip: Use get(), post(), put() or delete() instead

Parameters

- **method** (str) – the request method
- **url** (str) – the url to send the request to
- **payload** (Optional[dict]) – the JSON payload for the request (if the method is POST or PUT)

Return type
Response

get_logger(*log_file=None*, *stdout_level='INFO'*, *log_requests=True*)

Retrieve a MagentoLogger for the current username/domain combination. Log files are DEBUG.

Parameters

- **log_file** (Optional[str]) – the file to log to
- **stdout_level** (str) – the logging level for stdout logging
- **log_requests** (bool) – if True, adds the FileHandler to the connectionpool logger

Return type
MagentoLogger

property headers: dict

Authorization headers for API requests

Automatically generates a token if needed

property token: str

Returns or generates an ACCES_TOKEN

to_pickle(*validate=False*)

Serializes the Client to a pickle bytestring

Parameters
validate (bool) – if True, validates the token/USER_CREDENTIALS before serializing

Return type
bytes

to_json(*validate=False*)

Serializes the Client to a JSON string

Parameters
validate (bool) – if True, validates the token/USER_CREDENTIALS before serializing

Return type
str

to_dict(*validate=False*)

Serializes the Client to a dictionary

Parameters
validate (bool) – if True, validates the token/USER_CREDENTIALS before serializing

Return type
Dict[*str*, *str*]

view_config()

Prints the Client configuration settings

class magento.clients.**Store**(*client*)

Bases: object

Class containing store configurations and cached attribute lists

__init__(*client*)

Initialize a Store object

Parameters
client (Client) – an initialized Client object

property is_single_store: bool

Whether the store has a single store view (default) or multiple store views

property active: APIResponse

Returns the store config corresponding to the current scope of the Client

property configs: Optional[Union[APIResponse, List[APIResponse]]]

Returns a list of all store configurations

property views: Optional[Union[APIResponse, List[APIResponse]]]

Returns a list of all store views

property all_product_attributes: List[ProductAttribute]

A cached list of all product attributes

property store_view_product_attributes: List[ProductAttribute]

A cached list of all product attributes with the `Store View` scope

property website_product_attributes: List[ProductAttribute]

A cached list of all product attributes with the `Web Site` scope

property global_product_attributes: List[ProductAttribute]

A cached list of all product attributes with the `Global` scope

property website_attribute_codes: List[str]

The attribute codes of the `website_product_attributes`

filter_website_attrs(*attribute_data*)

Filters a product attribute dict and returns a new one that contains only the website scope attributes

Website scoped attributes must be updated on the admin by making a second request on the `all` scope

- This method is called by `update_attributes()` and `update_custom_attributes()` to see if the second request is needed

---

Example

The `price` attribute is `Website` scope and the `meta_title` attribute is `Store View` scope

```
>> attribute_data = {'price': 12, 'meta_title': 'My Product'}
>> store.filter_website_attrs(attribute_data)
{'price': 12}
```

Parameters
attribute_data (`dict`) – a dict of product attributes

Return type
dict

refresh()

Clears all cached properties

Return type
bool

3.2 The search module

Available Endpoints

The following endpoints are currently wrapped with a `Model` and `SearchQuery` subclass

Endpoint	Client Shortcut	SearchQuery Subclass	Model Subclass
orders	Client.orders	OrderSearch	Order
orders/items	Client.order_items	OrderItemSearch	OrderItem
invoices	Client.invoices	InvoiceSearch	Invoice
products	Client.products	ProductSearch	Product
products/attributes	Client.product_attributes	ProductAttributeSearch	ProductAttribute
categories	Client.categories	CategorySearch	Category
customers	Client.customers	CustomerSearch	Customer
endpoint	Client.search('endpoint')	SearchQuery	APIResponse

class magento.search.**SearchQuery**(*endpoint*, *client*, *model=<class 'magento.models.model.APIResponse'>*)

Bases: object

Queries any endpoint that invokes the searchCriteria interface. Parent of all endpoint-specific search classes

Tip: See https://developer.adobe.com/commerce/webapi/rest/use-rest/performing-searches/ for official docs

__init__(*endpoint*, *client*, *model=<class 'magento.models.model.APIResponse'>*)

Initialize a SearchQuery object

Parameters

- **endpoint** (str) – the base search API endpoint (for example, orders)
- **client** (Client) – an initialized Client object
- **model** (Type[Model]) – the Model to parse the response data with; uses APIResponse if not specified

client

The Client to send the search request with

endpoint

The endpoint being queried

Model

The magento.models subpackage class to wrap the response with

query

The current url for the search request

fields

Restricted fields, from restrict_fields()

add_criteria(*field*, *value*, *condition='eq'*, ***kwargs*)

Add criteria to the search query

Parameters

- **field** – the API response field to search by
- **value** – the value of the field to compare

- **condition** – the comparison condition
- **kwargs** – additional search option arguments (`group` and `filter`)

Returns
the calling SearchQuery object

Return type
Self

Keyword Argument Options: `Condition`

The `condition` argument specifies the condition used to evaluate the attribute value

- `"eq"` (default): matches items for which `field=value`
- `"gt"`: matches items for which `field>value`
- `"lt"`: matches items for which `field<value`
- `"gteq"`: matches items for which `field>=value`
- `"lteq"`: matches items for which `field<=value`
- `"in"`: matches items for which `field in value.split(",")`
  - Tip: for `in`, use `by_list()` if not building a complex query

Example

```
# Search for Orders created in 2023
>>> orders = api.orders.add_criteria(
...     field="created_at",
...     value="2023-01-01",
...     condition='gteq'
... ).execute()
```

Keyword Argument Options: Using Filter Groups

`group` - filter group number

`filter` - filter number (within the specified filter group)

Using Filter Groups

Filter groups are filter criteria in the form of { field: value }

Group 0 Filter 0 -> Filter 0 Group 0 Filter 0 + Group 0 Filter 1 -> Filter 0 OR Filter 1 Group 0 Filter 0 + Group 1 Filter 0 -> Filter 0 AND Filter 0

restrict_fields(*fields*)

Constrain the API response data to only contain the specified fields

Parameters
fields (`Iterable[str]`) – an iterable or comma separated string of fields to include in the response

Returns
the calling SearchQuery object

Return type
Self

execute()

Sends the search request using the current `scope` of the `client`

Tip: Change the `Client.scope` to retrieve `result` data from different store `views`

Returns
the search query `result`

Return type
Optional[*Union*[Model, *List*[Model]]]

by_id(*item_id*)

Retrieve data for an individual item by its id

Note: The `id` field used is different depending on the endpoint being queried

- Most endpoints use an `entity_id` or `id`
- The `orders/items` endpoint uses `item_id`
- The `products` endpoint uses `product_id`, but can also be queried `by_sku()`

The `IDENTIFIER` attribute of each `Model` contains the appropriate field

Parameters
item_id (`Union[int, str]`) – id of the item to retrieve

Return type
Optional[Model]

by_list(*field*, *values*)

Search for multiple items using an iterable or comma-separated string of field values

Examples

Retrieve `Product` with ids from 1 to 10:

```
# Values can be a list/tuple/iterable
>> api.products.by_list('entity_id', range(1,11))
```

Search for `Order` that are processing, pending, or completed:

```
#  Values can be a comma-separated string
>> api.orders.by_list('status', 'processing,pending,completed')
```

Parameters

- **field** (`str`) – the API response field to search for matches in

- **values** (Iterable) – an iterable or comma separated string of values

Return type
Optional[Model, *List*[Model]]

get_all()

Retrieve all items for the given search endpoint.

> **Warning:** Not guaranteed to work with all endpoints.

Return type
Optional[Model, *List*[Model]]

since(*sinceDate=None*)

Retrieve items for which `created_at >= sinceDate`

Example:

```
# Retrieve products created in 2023
>> api.products.since('2023-01-01').execute()
```

> **Tip:** Calling with no arguments retrieves all items

```
# Retrieve all products
>> api.products.since().execute()
```

Parameters
sinceDate (str) – the date for response data to start from

Returns
the calling SearchQuery

Return type
Self

until(*toDate*)

Retrieve items for which `created_at <= toDate`

Parameters
toDate (str) – the date for response data to end at (inclusive)

Returns
the calling SearchQuery

Return type
Self

property result: Optional[Union[Model, List[Model]]]

The result of the search query, wrapped by the Model corresponding to the endpoint

Returns
the API response as either an individual or list of Model objects

validate_result()

Parses the response and returns the actual result data, regardless of search approach

Return type
Optional[*Union*[*Dict*, *List*[*Dict*]]]

parse(*data*)

Parses the API response with the corresponding `Model` object

Parameters
data (`dict`) – API response data of a single item

Return type
Model

reset()

Resets the query and result, allowing the object to be reused

property result_count: int

Number of items that matched the search criteria

property result_type: Type

The type of the result

property last_group: int

The most recent filter group on the query

Returns
the most recent filter group, or `-1` if no criteria has been added

class magento.search.**OrderSearch**(*client*)

Bases: `SearchQuery`

`SearchQuery` subclass for the `orders` endpoint

__init__(*client*)

Initialize an `OrderSearch`

Parameters
client (`Client`) – an initialized `Client` object

by_number(*order_number*)

Retrieve an `Order` by number

Parameters
order_number (`Union[int, str]`) – the order number (`increment_id`)

Return type
Optional[Order]

by_product(*product*)

Search for all `Order` s of a `Product`

Parameters
product (`Product`) – the `Product` to search for in orders

Return type
Optional[*Union*[Order, *List*[Order]]]

by_sku(*sku*)

Search for `Order` by product sku

Note: Like `OrderItemSearch.by_sku()`, the sku will need to be an exact match to the sku of a simple product, including a custom option if applicable

- Use `by_product()` or `by_product_id()` to find orders containing any of the `option_skus` and/or all `children` of a configurable product

---

Parameters
sku (`str`) – the exact product sku to search for in orders

Return type
Optional[*Union*[Order, *List*[Order]]]

by_product_id(*product_id*)

Search for `Order` s by `product_id`

Parameters
product_id (`Union[int, str]`) – the `id` (`product_id`) of the product to search for in orders

Return type
Optional[*Union*[Order, *List*[Order]]]

by_category_id(*category_id*, *search_subcategories=False*)

Search for `Order` s by `category_id`

Parameters

- **category_id** (`Union[int, str]`) – id of the category to search for in orders
- **search_subcategories** (`bool`) – if `True`, also searches for orders from `all_subcategories`

Returns
any `Order` containing a `Product` in the corresponding `Category`

Return type
Optional[*Union*[Order, *List*[Order]]]

by_category(*category*, *search_subcategories=False*)

Search for `Order` s that contain any of the category's `products`

Parameters

- **category** (`Category`) – the `Category` to use in the search
- **search_subcategories** (`bool`) – if `True`, also searches for orders from `all_subcategories`

Returns
any `Order` that contains a product in the provided category

Return type
Optional[*Union*[Order, *List*[Order]]]

by_skulist(*skulist*)

Search for `Order` s using a list or comma separated string of product SKUs

Parameters
skulist (Union[str, Iterable[str]]) – an iterable or comma separated string of product SKUs

Return type
Optional[*Union*[Order, *List*[Order]]]

by_customer(*customer*)

Search for Order s by Customer

Parameters
customer (Customer) – the Customer to retrieve orders from

Return type
Optional[*Union*[Order, *List*[Order]]]

by_customer_id(*customer_id*)

Search for Order s by customer_id

Parameters
customer_id (Union[int, str]) – the id of the customer to retrieve orders for

Return type
Optional[*Union*[Order, *List*[Order]]]

from_items(*items*)

Retrieve unique Order objects from OrderItem entries using a single request

Parameters
items (Optional[OrderItem | List[OrderItem]]) – an individual/list of order items

Return type
Optional[Order, *List*[Order]]

class magento.search.**OrderItemSearch**(*client*)

Bases: SearchQuery

SearchQuery subclass for the orders/items endpoint

__init__(*client*)

Initialize an OrderItemSearch

Parameters
client (Client) – an initialized Client object

property result: Optional[Union[OrderItem, List[OrderItem]]]

The result of the search query, wrapped by the Model corresponding to the endpoint

Returns
the API response as either an individual or list of Model objects

parse(*data*)

Overrides SearchQuery.parse() to fully hydrate OrderItem objects

Extra validation is required for OrderItems, as duplicated and/or incomplete data is returned when the child of a configurable product is searched by_sku() or by_product()

Parameters
data – API response data

Return type
Optional[OrderItem]

by_product(*product*)

Search for `OrderItem` entries by `Product`

Note: This will match OrderItems that contain

- Any of the child products of a configurable product
- Any of the `option_skus` of a product with custom options

Parameters
product (`Product`) – the `Product` to search for in order items

Return type
Optional[*Union*[OrderItem, *List*[OrderItem]]]

by_sku(*sku*)

Search for `OrderItem` entries by product sku.

The SKU must be an exact match to the OrderItem SKU

OrderItems always use the SKU of a simple product, including any custom options. This means that:

- Searching the SKU of a configurable product returns nothing
- If a product has custom options, the search will only find OrderItems that contain the specific option sku (or base sku) that's provided

To search for OrderItems containing all `children` of a configurable product and/or all possible `option_skus`, use `by_product()` or `by_product_id()`

Parameters
sku (`str`) – the exact product sku to search for in order items

Return type
Optional[*Union*[OrderItem, *List*[OrderItem]]]

by_product_id(*product_id*)

Search for `OrderItem` entries by product id.

Parameters
product_id (`Union[int, str]`) – the `id` (`product_id`) of the `Product` to search for in order items

Return type
Optional[*Union*[OrderItem, *List*[OrderItem]]]

by_category_id(*category_id*, *search_subcategories=False*)

Search for `OrderItem` entries by `category_id`

Parameters

- **category_id** (`Union[int, str]`) – id of the `Category` to search for in order items

- **search_subcategories** (bool) – if True, also searches for order items from all_subcategories

Returns
any OrderItem containing a Product in the corresponding Category

Return type
Optional[*Union*[OrderItem, *List*[OrderItem]]]

by_category(*category*, *search_subcategories=False*)

Search for OrderItem entries that contain any of the category's products

Parameters

- **category** (Category) – the Category to use in the search
- **search_subcategories** (bool) – if True, also searches for order items from all_subcategories

Return type
Optional[*Union*[OrderItem, *List*[OrderItem]]]

by_skulist(*skulist*)

Search for :class:`~.OrderItem`s using a list or comma-separated string of product SKUs

Parameters
skulist (Union[str, Iterable[str]]) – an iterable or comma separated string of product SKUs

Return type
Optional[*Union*[OrderItem, *List*[OrderItem]]]

class magento.search.**InvoiceSearch**(*client*)

Bases: SearchQuery

SearchQuery subclass for the invoices endpoint

__init__(*client*)

Initialize an InvoiceSearch

Parameters
client (Client) – an initialized Client object

by_number(*invoice_number*)

Retrieve an Invoice by number

Parameters
invoice_number (Union[int, str]) – the invoice number (increment_id)

Return type
Optional[Invoice]

by_order_number(*order_number*)

Retrieve an Invoice by order number

Parameters
order_number (Union[int, str]) – the order number (increment_id)

Return type
Optional[Invoice]

by_order(*order*)

Retrieve the `Invoice` for an `Order`

Parameters
order (`Order`) – the `Order` object to retrieve an invoice for

Return type
Optional[Invoice]

by_order_id(*order_id*)

Retrieve an `Invoice` by `order_id`

Parameters
order_id (`Union[int, str]`) – the `order_id` of the order to retrieve an invoice for

Return type
Optional[Invoice]

by_product(*product*)

Search for all `Invoice` s of a `Product`

Parameters
product (`Product`) – the `Product` to search for in invoices

Return type
Optional[*Union*[Invoice, *List*[Invoice]]]

by_sku(*sku*)

Search for `Invoice` s by product sku

Note: Like `OrderItemSearch.by_sku()`, the sku will need to be an exact match to the sku of a simple product, including a custom option if applicable

- Use `by_product()` or `by_product_id()` to find orders containing any of the `option_skus` and/or all `children` of a configurable product

---

Parameters
sku (`str`) – the exact product sku to search for in invoices

Return type
Optional[*Union*[Invoice, *List*[Invoice]]]

by_product_id(*product_id*)

Search for `Invoice` s by `product_id`

Parameters
product_id (`Union[int, str]`) – the `id` (`product_id`) of the product to search for in invoices

Return type
Optional[*Union*[Invoice, *List*[Invoice]]]

by_category_id(*category_id*, *search_subcategories=False*)

Search for `Invoice` s by `category_id`

Parameters

- **category_id** (`Union[int, str]`) – id of the category to search for in orders

- **search_subcategories** (bool) – if True, also searches for orders from all_subcategories

Returns
any Invoice containing a Product in the corresponding Category

Return type
Optional[*Union*[Invoice, *List*[Invoice]]]

by_category(*category*, *search_subcategories=False*)

Search for Invoice s that contain any of the category's products

Parameters

- **category** (Category) – the Category to use in the search
- **search_subcategories** (bool) – if True, also searches for orders from all_subcategories

Returns
any Invoice that contains a product in the provided category

Return type
Optional[*Union*[Invoice, *List*[Invoice]]]

by_skulist(*skulist*)

Search for Invoice s using a list or comma separated string of product SKUs

Parameters
skulist (Union[str, Iterable[str]]) – an iterable or comma separated string of product SKUs

Return type
Optional[*Union*[Invoice, *List*[Invoice]]]

by_customer(*customer*)

Search for all Invoice s of a Customer

Parameters
customer (Customer) – the Customer to search for in invoices

Returns
any Invoice associated with the provided Customer

Return type
Optional[*Union*[Invoice, *List*[Invoice]]]

by_customer_id(*customer_id*)

Search for Invoice s by customer_id

Parameters
customer_id (Union[int, str]) – the id of the customer to retrieve invoices for

Return type
Optional[*Union*[Invoice, *List*[Invoice]]]

from_order_items(*items*)

Retrieve unique Invoice objects from OrderItem entries using a single request

Tip: Since there is no invoices/items endpoint, to search for invoices we must first do an OrderItemSearch, then retrieve the order_ids and search by_order_id()

Parameters
items (Optional[OrderItem | List[OrderItem]]) – an individual/list of order items

Return type
Optional[Invoice, *List*[Invoice]]

class magento.search.**ProductSearch**(*client*)

Bases: SearchQuery

SearchQuery subclass for the products endpoint

__init__(*client*)

Initialize a ProductSearch

Parameters
client (Client) – an initialized Client object

property attributes: ProductAttributeSearch

Alternate way to access the SearchQuery for ProductAttribute data

by_id(*item_id*)

Retrieve a Product by product_id

Note: Response data from the products endpoint only has an id field, but all other endpoints that return data about products will use product_id

---

Parameters
item_id (Union[int, str]) – the id (product_id) of the product

Return type
Optional[Product]

by_sku(*sku*)

Retrieve a Product by sku

Parameters
sku – the product sku

Return type
Optional[Product]

by_skulist(*skulist*)

Search for :class:` ~.Product`s using a list or comma separated string of SKUs

Parameters
skulist (Union[str, Iterable[str]]) – an iterable or comma separated string of SKUs

Return type
Optional[*Union*[Product, *List*[Product]]]

by_category(*category*, *search_subcategories=False*)

Search for Product s in a Category

Parameters

- **category** (Category) – the Category to retrieve products from

- **search_subcategories** (bool) – if True, also retrieves products from all_subcategories

Return type
Optional[*Union*[Product, *List*[Product]]]

by_category_id(*category_id*, *search_subcategories=False*)

Search for Product s by category_id

Parameters

- **category_id** (Union[int, str]) – the id of the Category to retrieve products from
- **search_subcategories** (bool) – if True, also retrieves products from all_subcategories

Return type
Optional[*Union*[Product, *List*[Product]]]

by_customer_id(*customer_id*, *exclude_cancelled=True*)

Search for ordered Products by customer_id

Parameters

- **customer_id** (Union[int, str]) – the id of the customer to retrieve ordered products for
- **exclude_cancelled** (bool) – flag indicating if products from cancelled orders should be excluded

Returns
products that the customer has ordered, as an individual or list of Product objects

get_stock(*sku*)

Retrieve the stock of a product by sku

Parameters
sku – the product sku

Return type
Optional[*int*]

class magento.search.**ProductAttributeSearch**(*client*)

Bases: SearchQuery

SearchQuery subclass for the products/attributes endpoint

__init__(*client*)

Initialize a ProductAttributeSearch

Parameters
client (Client) – an initialized Client object

get_all()

Retrieve a list of all :class:`~.ProductAttribute`s

Return type
Optional[*List*[ProductAttribute]]

by_code(*attribute_code*)

Retrieve a ProductAttribute by its attribute code

Parameters
attribute_code (str) – the code of the ProductAttribute

Return type
Optional[ProductAttribute]

get_types()

Retrieve a list of all available ProductAttribute types

Return type
Optional[*List*[APIResponse]]

class magento.search.**CustomerSearch**(*client*)

Bases: SearchQuery

SearchQuery subclass for the customers/search endpoint

__init__(*client*)

Initialize a CustomerSearch

Parameters
client (Client) – an initialized Client object

by_id(*item_id*)

Retrieve data for an individual item by its id

Note: The id field used is different depending on the endpoint being queried

- Most endpoints use an entity_id or id
- The orders/items endpoint uses item_id
- The products endpoint uses product_id, but can also be queried by_sku()

The IDENTIFIER attribute of each Model contains the appropriate field

Parameters
item_id (Union[int, str]) – id of the item to retrieve

Return type
Optional[Customer]

by_first_name(*name*)

by_last_name(*name*)

by_invoice(*invoice*)

by_order(*order*)

by_product(*product*)

Return type
Optional[*Union*[Customer, *List*[Customer]]]

class magento.search.**CategorySearch**(*client*)

Bases: `SearchQuery`

`SearchQuery` subclass for the `categories` endpoint

__init__(*client*)

Initialize a `CategorySearch`

Parameters
client (`Client`) – an initialized `Client` object

get_root()

Retrieve the top level/default `Category` (every other category is a subcategory)

Return type
Category

get_all()

Retrieve a list of all categories

Return type
List[Category]

by_name(*name*, *exact=True*)

Search for a `Category` by name

Parameters

- **name** (`str`) – the category name to search for
- **exact** (`bool`) – whether the name should be an exact match

Return type
Optional[*Union*[Category, *List*[Category]]]

3.3 The exceptions module

exception magento.exceptions.**MagentoError**(*client*, *msg=None*, *response=None*)

Bases: `Exception`

Base exception class for error responses returned by the Magento API

Variables
DEFAULT_MSG – default exception message to use if a message isn't provided

DEFAULT_MSG = 'An error occurred while processing the request.'

__init__(*client*, *msg=None*, *response=None*)

Log and raise a MagentoError

Parameters

- **client** (`Client`) – an initialized `Client` object

- **msg** (Optional[str]) – optional exception message; prepended to the error message of the response
- **response** (Optional[Response]) – optional response to parse() an error message from

static parse(*response*)

Parses the error message from the response

Parameters
response (Union[Response, Dict]) – a bad response returned by the Magento API

Raises
TypeError if response is not a Response or Dict

Return type
str

exception magento.exceptions.**AuthenticationError**(*client*, *msg=None*, *response=None*)

Bases: MagentoError

Exception class for errors when trying to authenticate() a Client

DEFAULT_MSG = 'Failed to authenticate credentials.'

__init__(*client*, *msg=None*, *response=None*)

Log and raise a MagentoError

Parameters

- **client** (Client) – an initialized Client object
- **msg** (Optional[str]) – optional exception message; prepended to the error message of the response
- **response** (Optional[Response]) – optional response to parse() an error message from

3.4 The utils module

magento.utils.**parse_domain**(*domain*)

Returns the root domain of the provided domain

Example:

```
>>> parse_domain('https://www.mymagento.com#new-products')
'mymagento.com'

>>> parse_domain('https://username:password@my-magento.mymagento.com:443/store')
'my-magento.mymagento.com'

>>> parse_domain('127.0.0.1/path/to/magento/')
'127.0.0.1/path/to/magento'
```

magento.utils.**get_agents**()

Scrapes a list of user agents. Returns a default list if the scrape fails.

Return type
list

magento.utils.**get_agent**(*index=0*)

Returns a single user agent string from the specified index of the AGENTS list

Return type
str

class magento.utils.**LoggerUtils**

Bases: object

Utility class that simplifies access to logger handler info

static get_handler_names(*logger*)

Get all handler names

Return type
List[*str*]

static get_stream_handlers(*logger*)

Get all the StreamHandlers of the current logger (NOTE: StreamHandler subclasses excluded)

Return type
List[*Handler*]

static get_file_handlers(*logger*)

Get all the FileHandlers of the current logger

Return type
List[*FileHandler*]

static get_log_files(*logger*)

Get the log file paths from all FileHandlers of a logger

Return type
List[*str*]

static get_handler_by_log_file(*logger*, *log_file*)

Returns the FileHandler logging to the specified file, given it exists

Return type
Union[*FileHandler*, *List*[*FileHandler*]]

static clear_handlers(*logger*)

Return type
bool

static clear_stream_handlers(*logger*)

Removes all StreamHandlers from a logger

Return type
bool

static clear_file_handlers(*logger*)

Removes all FileHandlers from a logger

Return type
bool

static map_handlers_by_name(*logger*)

Map the handlers of a logger first by type, and then by their name

FileHandlers are mapped to both their handlers and log file, while StreamHandlers are just mapped to the handler Handlers without a name will be skipped, because look at the method name (:

class magento.utils.**MagentoLogger**(*name*, *log_file=None*, *stdout_level='INFO'*, *log_requests=True*)

Bases: object

Logging class used within the package

Variables

- **PREFIX** – hardcoded prefix to use in log messages
- **PACKAGE_LOG_NAME** – the default name for the package logger
- **CLIENT_LOG_NAME** – the default format for the client logger name
- **LOG_MESSAGE** – the default format for the message component of log messages. (Use magento.logger.LOG_MESSAGE for easy access)
- **FORMATTER** – the default logging format
- **HANDLER_NAME** – the default format for the names of handlers created by this package

PREFIX = 'MyMagento'

PACKAGE_LOG_NAME = 'my-magento'

CLIENT_LOG_NAME = '{domain}_{username}'

HANDLER_NAME = 'MyMagento__{name}__{stdout_level}'

LOG_MESSAGE = '|[MyMagento | {name}]|: {message}'

FORMATTER = <logging.Formatter object>

__init__(*name*, *log_file=None*, *stdout_level='INFO'*, *log_requests=True*)

Initialize the logger

Each Client object corresponds to a unique username/domain combination, which is used to attach it to its associated MagentoLogger and log file, allowing all activity across all endpoints to be tracked. A package logger exists as well, which logs all activity from the package. All log files have their log level set to DEBUG

Parameters

- **name** (str) – logger name
- **log_file** (Optional[str]) – log file name; default is {name}.log
- **stdout_level** (Union[int, str]) – logging level for stdout logger; default is "INFO" (which is also logging.INFO and 10)
- **log_requests** (bool) – set to True to add logging from the requests package logger

setup_logger(*stdout_level='INFO'*, *log_requests=True*)

Configures a logger and assigns it to the *logger* attribute.

Parameters

- **stdout_level** (Union[int, str]) – logging level to use for logging to console
- **log_requests** (bool) – set to True to add logs from the requests package (ie. API call logging)

Return type
bool

format_msg(*msg*)

Formats the LOG_MESSAGE using the specified message

Return type
str

debug(*msg*)

Formats the LOG_MESSAGE with the specified message, then logs it with Logger.debug()

info(*msg*)

Formats the LOG_MESSAGE with the specified message, then logs it with Logger.info()

error(*msg*)

Formats the LOG_MESSAGE with the specified message, then logs it with Logger.error()

warning(*msg*)

Formats the LOG_MESSAGE with the specified message, then logs it with Logger.warning()

critical(*msg*)

Formats the LOG_MESSAGE with the specified message, then logs it with Logger.critical()

property handlers

property handler_names

property handler_map

property file_handlers

property stream_handlers

property log_files

property log_path

static get_magento_handlers(*logger*)

static clear_magento_handlers(*logger*, *handler_type*, *clear_pkg=False*)

Clear all handlers from a logger that were created by MagentoLogger

Parameters

- **logger** (Logger) – any logger
- **handler_type** (Union[Type[FileHandler], Type[StreamHandler]]) – the logging handler type to check for and remove
- **clear_pkg** (bool) – if True, will delete the package handler for writing to mymagento.log (Default is False)

static clear_magento_file_handlers(*logger*, *clear_pkg=False*)

static clear_magento_stdout_handlers(*logger*, *clear_pkg=False*)

static owns_handler(*handler*)

Checks if a handler is a Stream/FileHandler from this package or not

static get_package_handler()

Returns the FileHandler object that writes to the magento.log file

Return type
FileHandler

static add_request_logging(*handler*)

Adds the specified handler to the requests package logger, allowing for easier debugging of API calls

magento.utils.**get_package_file_handler**()

...

The magento.models Subpackage

- The model module
- The product module
- The category module
- The order module
- The invoice module

CHAPTER

FOUR

THE MAGENTO.MODELS SUBPACKAGE

The magento.models subpackage contains all of the Model API response wrapper classes.

4.1 The model module

class magento.models.model.**Model**(*data*, *client*, *endpoint*, *private_keys=True*)

Bases: ABC

The abstract base class of all API response wrapper classes

Overview

- A Model wraps the response data from an API endpoint
- Several endpoints have subclasses with additional methods to retrieve/update data
- All other endpoints are wrapped using a general APIResponse
- The endpoint's corresponding SearchQuery can be accessed via query_endpoint()

DOCUMENTATION: str = None

Link to the Official Magento 2 API documentation for the endpoint wrapped by the Model

IDENTIFIER: str = None

The API response field that the endpoint's uid comes from

__init__(*data*, *client*, *endpoint*, *private_keys=True*)

Initialize a Model object from an API response and the endpoint that it came from

...

Tip: The endpoint is used to:

- Generate the url_for() any requests made by subclass-specific methods
- Match the Model to its corresponding SearchQuery object
- Determine how to parse() new Model objects from API responses

---

...

Parameters

- **data** (dict) – the JSON from an API response to use as source data
- **client** (Client) – an initialized Client
- **endpoint** (str) – the API endpoint that the Model wraps
- **private_keys** (bool) – if True, sets the keys in the excluded_keys as private attributes (prefixed with __) instead of fully excluding them

set_attrs(*data*, *private_keys=True*)

Initializes object attributes using the JSON from an API response as the data source

Called at the time of object initialization, but can also be used to update the source data and reinitialize the attributes without creating a new object

Parameters

- **data** (dict) – the API response JSON to use as the object source data
- **private_keys** (bool) – if set to True, will set the excluded_keys as private attributes (prefixed with __) instead of fully excluding them

---

Private Keys Clarification

Let's say that "status" is in the excluded_keys

- No matter what, the status attribute will not be set on the Model
- If private_keys==True, the __status attribute will be set (using the status data)
- If private_keys==False, the data from status is completely excluded

---

abstract property excluded_keys: List[str]

API response keys that shouldn't be set as object attributes by set_attrs()

Returns
list of API response keys that shouldn't be set as attributes

property uid: Union[str, int]

Unique item identifier; used in the url of the data_endpoint()

data_endpoint(*scope=None*)

Endpoint to use when requesting/updating the item's data

Parameters
scope (Optional[str]) – the scope to generate the url_for()

Return type
str

query_endpoint()

Initializes and returns the SearchQuery object corresponding to the Model's endpoint

Returns
a SearchQuery or subclass, depending on the endpoint

Return type
SearchQuery

parse(*response*)

Uses the instance's corresponding SearchQuery to parse an API response

Parameters
response (dict) – API response dict to use as source data

Returns
a Model with the same endpoint as the calling instance

Return type
Model

refresh(*scope=None*)

Updates object attributes in place using current data from the data_endpoint()

Hint: refresh() can be used to switch the scope of the source data without creating a new object or changing the Client.scope

---

Example

```
# Get product data on 'default' scope
>>> product = client.products.by_sku('sku42')
# Get fresh product data from different scope
>>> product.refresh('all')

Refreshed <Magento Product: sku42> on scope all
```

Parameters
scope (Optional[str]) – the scope to send the request on; uses the Client.scope if not provided

Return type
bool

static unpack_attributes(*attributes*, *key='attribute_code'*)

Unpacks a list of attribute dictionaries into a single dictionary

---

Example

```
>> custom_attrs = [{'attribute_code': 'attr', 'value': 'val'},{'attribute_code':
↪'will_to_live', 'value': '0'}]
>> print(Model.unpack_attributes(custom_attrs))

{'attr': 'val', 'will_to_live': '0'}
```

Parameters

- **attributes** (List[dict]) – a list of custom attribute dictionaries
- **key** (str) – the key used in the attribute dictionary (ex. attribute_code or label)

Returns
a single dictionary of all custom attributes formatted as {"attr": "val"}

Return type
dict

static pack_attributes(*attribute_data*, *key='attribute_code'*)

Packs a dictionary containing attributes into a list of attribute dictionaries

Example

```
>> attribute_data = {'special_price': 12, 'meta_title': 'My Product'}
>> print(Model.pack_attributes(attribute_data))
>> print(Model.pack_attributes(attribute_data, key='label'))

[{'attribute_code': 'special_price', 'value': 12}, {'attribute_code': 'meta_title',
↪'value': 'My Product'}]
[{'label': 'special_price', 'value': 12}, {'label': 'meta_title', 'value': 'My␣
↪Product'}]
```

Parameters

- **attribute_data** (dict) – a dictionary containing attribute data
- **key** (str) – the key to use when packing the attributes (ex. attribute_code or label)

Returns
a list of dictionaries formatted as {key : "attr", "value": "value"}

Return type
List[*dict*]

static encode(*string*)

URL-encode with urllib.parse; used for requests that could contain special characters

Parameters
string (str) – the string to URL-encode

Return type
str

property cached: List[str]

Names of properties that are wrapped with functools.cached_property()

clear(**keys*)

Deletes the provided keys from the object's __dict__

To clear all cached properties:

```
>> self.clear(*self.cached)
```

Parameters
keys (str) – name of the object attribute(s) to delete

get_scope_name(*scope*)

Returns the appropriate scope name to use for logging messages

Return type
str

...

class magento.models.model.**APIResponse**(*data*, *client*, *endpoint*)

Bases: Model

IDENTIFIER: str = 'entity_id'

The API response field that the endpoint's uid comes from

__init__(*data*, *client*, *endpoint*)

A generic Model subclass

Wraps API responses when there isn't a Model subclass defined for the endpoint

Parameters

- **data** (dict) – the API response from an API endpoint
- **client** (Client) – an initialized Client object
- **endpoint** (str) – the endpoint that the API response came from

property excluded_keys: List[str]

API response keys that shouldn't be set as object attributes by set_attrs()

Returns
list of API response keys that shouldn't be set as attributes

property uid: Optional[int]

Unique item identifier

Note: Since the APIResponse can wrap any endpoint, the response is checked for commonly used id fields (entity_id and id)

If the endpoint doesn't use those fields, None will be returned

---

data_endpoint(*scope=None*)

Endpoint to use when requesting/updating the item's data

Parameters
scope (Optional[str]) – the scope to generate the url_for()

Return type
Optional[*str*]

4.2 The product module

class magento.models.product.**Product**(*data*, *client*)

Bases: Model

Wrapper for the products endpoint

STATUS_ENABLED = 1

STATUS_DISABLED = 2

VISIBILITY_NOT_VISIBLE = 1

VISIBILITY_CATALOG = 2

VISIBILITY_SEARCH = 3

VISIBILITY_BOTH = 4

DOCUMENTATION: str = 'https://adobe-commerce.redoc.ly/2.3.7-admin/tag/products/'

Link to the Official Magento 2 API documentation for the endpoint wrapped by the Model

IDENTIFIER: str = 'sku'

The API response field that the endpoint's `uid` comes from

__init__(*data*, *client*)

Initialize a Product object using an API response from the `products` endpoint

Parameters

- **data** (`dict`) – the API response from the `products` endpoint
- **client** (`Client`) – an initialized `Client` object

property excluded_keys

API response keys that shouldn't be set as object attributes by `set_attrs()`

Returns
list of API response keys that shouldn't be set as attributes

update_stock(*qty*)

Updates the stock quantity

Parameters
qty (`int`) – the new stock quantity

Return type
bool

update_status(*status*)

Update the product status

Parameters
status (`int`) – either 1 (for `STATUS_ENABLED`) or 2 (for `STATUS_DISABLED`)

Return type
bool

update_price(*price*)

Update the product price

Parameters
price (`Union[int, float]`) – the new price

Return type
bool

update_special_price(*price*)

Update the product special price

Parameters
price (Union[float, int]) – the new special price

Return type
bool

update_name(*name*, *scope=None*)

Update the product name

Parameters

- **name** (str) – the new name to use
- **scope** (Optional[str]) – the scope to send the request on; will use the Client.scope if not provided

Return type
bool

update_description(*description*, *scope=None*)

Update the product description

Parameters

- **description** (str) – the new HTML description to use
- **scope** (Optional[str]) – the scope to send the request on; will use the Client.scope if not provided

Return type
bool

update_metadata(*metadata*, *scope=None*)

Update the product metadata

Parameters

- **metadata** (dict) – the new meta_title, meta_keyword and/or meta_description to use
- **scope** (Optional[str]) – the scope to send the request on; will use the Client.scope if not provided

Return type
bool

add_categories(*category_ids*)

Adds the product to an individual or multiple categories

Parameters
category_ids (Union[int, str, List[Union[int, str]]]) – an individual or list of category IDs to add the product to

Return type
bool

remove_categories(*category_ids*)

Removes the product from an individual or multiple categories

Parameters
category_ids (Union[int, str, List[Union[int, str]]]) – an individual or list of category IDs to remove the product from

Return type
bool

update_attributes(*attribute_data*, *scope=None*)

Update top level product attributes with scoping taken into account

---

Note: Product attributes can have a `Global`, `Store View` or `Website` scope

Global Attributes
Values are updated on all store views and the admin

Website Attributes
Values are updated on all store views

Store View Attributes
Values are updated on the store view specified in the request `scope`

A second request will be made to update `Store View` and `Website` attributes on the admin, depending on how many `Store views` you have:

- **1 View:** admin values are updated for all attributes, regardless of scope
- **2+ Views:** admin values are updated only for `website_product_attributes`

Parameters

- **attribute_data** (dict) – a dictionary of product attributes to update
- **scope** (Optional[str]) – the scope to send the request on; will use the `Client.scope` if not provided

Return type
bool

update_custom_attributes(*attribute_data*, *scope=None*)

Update custom attributes with scoping taken into account

See `update_attributes()` for details

Important

This method only supports updating **custom attributes**

Parameters

- **attribute_data** (dict) – a dictionary of custom attributes to update
- **scope** (Optional[str]) – the scope to send the request on; will use the `Client.scope` if not provided

Return type
bool

add_product_link(*link_type*, *linked_sku*, *position=None*)

Adds or updates a related, up-sell, or cross-sell product link.

Note: If the product link already exists for the provided SKU, this method will only update the link if a `position` is specified.

Parameters

- **link_type** (`str`) – the product link type; must be `upsell`, `related` or `crosssell`
- **linked_sku** (`str`) – the SKU of the product to be linked
- **position** (`Optional[int]`) – the position of the product link; if not provided, it will be added as the last link.

Returns

boolean indicating success of the operation.

Return type

bool

delete_product_link(*link_type*, *linked_sku*)

Removes a related, up-sell, or cross-sell product link.

Parameters

- **link_type** (`str`) – the product link type; must be `upsell`, `related` or `crosssell`
- **linked_sku** (`str`) – the SKU of the product link to remove

Returns

boolean indicating success of the operation.

Return type

bool

get_orders()

Searches for orders that contain the product

If the product is configurable, returns orders containing any of its child products

Returns

orders that contain the product, as an individual or list of `Order` objects

Return type

Optional[Order | *List*[Order]]

get_order_items()

Searches for order items that contain the product

If the product is configurable, returns order items containing any of its child products

Returns

order items that contain the product, as an individual or list of `OrderItem` objects

Return type

Optional[OrderItem | *List*[OrderItem]]

get_invoices()

Searches for invoices that contain the product

If the product is configurable, returns invoices containing any of its child products

Returns
invoices that contain the product, as an individual or list of `Invoice` objects

Return type
Optional[Invoice | *List*[Invoice]]

get_customers()

Searches for customers that have ordered the product

If the product is configurable, returns customers that have ordered any of its child products

Returns
customers that have ordered the product, as an individual or list of `Customer` objects

Return type
Optional[Customer | *List*[Customer]]

delete()

Deletes the product

Hint: If you delete a product by accident, the `Product` object's `data` attribute will still contain the raw data, which can be used to recover it.

Alternatively, don't delete it by accident.

Return type
bool

get_product_links(*link_type*)

Returns data for all product links of the specified type

Parameters
link_type (`str`) – the product link type; must be `upsell`, `related` or `crosssell`

Return type
List[*Dict*]

get_children(*refresh=False*, *scope=None*)

Retrieve the child simple products of a configurable product

Parameters

- **refresh** (`bool`) – if True, calls `refresh()` on the child products to retrieve full data
- **scope** (`Optional[str]`) – the scope to refresh the children on (when `refresh=True`)

Return type
List[Product]

property children: List[Product]

If the Product is a configurable product, returns a list of its child products

property link: str

Link of the product

property categories: Optional[Category | List[Category]]

Categories the product is in, returned as a list of `Category` objects

property media_gallery_entries: List[MediaEntry]

The product's media gallery entries, returned as a list of `MediaEntry` objects

property thumbnail: MediaEntry

The `MediaEntry` corresponding to the product's thumbnail

property thumbnail_link: str

Link of the product's `thumbnail` image

get_media_by_id(*entry_id*)

Access a `MediaEntry` of the product by id

Parameters
entry_id (`int`) – the id of the media gallery entry

Return type
MediaEntry

property encoded_sku: str

URL-encoded SKU, which is used in request endpoints

property option_skus: List[str]

The full SKUs for the product's customizable options, if they exist

---

Hint: When a product with customizable options is ordered, these SKUs are used by the API when retrieving and searching for `Order` and `OrderItem` data

---

property stock: int

Current stock quantity

property stock_item: dict

Stock data from the StockItem Interface

property stock_item_id: int

Item id of the StockItem, used to `update_stock()`

property description: str

Product description (as HTML)

property special_price: float

The current special (sale) price

class magento.models.product.**MediaEntry**(*product*, *entry*)

Bases: `Model`

Wraps a media gallery entry of a `Product`

MEDIA_TYPES = ['base', 'small', 'thumbnail', 'swatch']

DOCUMENTATION: str =
'https://adobe-commerce.redoc.ly/2.3.7-admin/tag/productsskumediaentryId'

Link to the Official Magento 2 API documentation for the endpoint wrapped by the Model

IDENTIFIER: str = 'id'

The API response field that the endpoint's `uid` comes from

__init__(*product*, *entry*)

Initialize a MediaEntry object for a `Product`

Parameters

- **product** (`Product`) – the `Product` that the gallery entry is associated with
- **entry** (`dict`) – the json response data to use as the source data

query_endpoint()

No search endpoint exists for media gallery entries

property excluded_keys: List[str]

API response keys that shouldn't be set as object attributes by `set_attrs()`

Returns

list of API response keys that shouldn't be set as attributes

property is_enabled

property is_thumbnail

property link

Permalink to the image

disable(*scope=None*)

Disables the MediaEntry on the given scope

Parameters

scope (`Optional[str]`) – the scope to send the request on; will use the `Client.scope` if not provided

Return type

bool

enable(*scope=None*)

Enables the MediaEntry on the given scope

Parameters

scope (`Optional[str]`) – the scope to send the request on; will use the `Client.scope` if not provided

Return type

bool

download(*filename=None*)

Downloads the MediaEntry image

Parameters

filename (`Optional[str]`) – the name of the file to save the image to; uses the filename on Magento if not provided.

Returns

the absolute path of the downloaded image file, or `None` if the download failed

Return type

Optional[*str*]

add_media_type(*media_type*, *scope=None*)

Add a media type to the MediaEntry on the given scope

> **Caution:** If the media type is already assigned to a different entry, it will be removed

Parameters

- **media_type** (`str`) – one of the `MEDIA_TYPES`
- **scope** (`Optional[str]`) – the scope to send the request on; will use the `Client.scope` if not provided

Return type
bool

remove_media_type(*media_type*, *scope=None*)

Remove a media type from the MediaEntry on the given scope

Parameters

- **media_type** (`str`) – one of the `MEDIA_TYPES`
- **scope** (`Optional[str]`) – the scope to send the request on; will use the `Client.scope` if not provided

Return type
bool

set_media_types(*types*, *scope=None*)

Set media types for the MediaEntry on the given scope

Parameters

- **types** (`list`) – a list containing all `MEDIA_TYPES` to assign
- **scope** (`Optional[str]`) – the scope to send the request on; will use the `Client.scope` if not provided

Return type
bool

set_position(*position*, *scope=None*)

Set the position of the MediaEntry on the given scope

Parameters

- **position** (`int`) – the position to change to
- **scope** (`Optional[str]`) – the scope to send the request on; will use the `Client.scope` if not provided

Return type
bool

set_alt_text(*text*, *scope=None*)

Set the alt text (`label`) of the MediaEntry on the given scope

Parameters

- **text** (`str`) – the alt text to use

- **scope** (Optional[str]) – the scope to send the request on; will use the Client.scope if not provided

Return type
bool

update(*scope=None*)

Uses the data dict to update the media entry

Note: Some updates alter the data of other entries; if the update is successful, the associated Product will be refreshed on the same scope to keep the data consistent

Tip: If there's only 1 store view, the admin will also be updated

Parameters
scope (Optional[str]) – the scope to send the request on; will use the Client.scope if not provided

Return type
bool

class magento.models.product.**ProductAttribute**(*data*, *client*)

Bases: Model

Wrapper for the products/attributes endpoint

DOCUMENTATION: str = 'https://adobe-commerce.redoc.ly/2.3.7-admin/tag/productsattributes/'

Link to the Official Magento 2 API documentation for the endpoint wrapped by the Model

IDENTIFIER: str = 'attribute_code'

The API response field that the endpoint's uid comes from

__init__(*data*, *client*)

Initialize a ProductAttribute object using an API response from the products/attributes endpoint

Parameters

- **data** (dict) – the API response from the products/attributes endpoint
- **client** (Client) – an initialized Client object

property excluded_keys: List[str]

API response keys that shouldn't be set as object attributes by set_attrs()

Returns
list of API response keys that shouldn't be set as attributes

property options

4.3 The category module

class magento.models.category.**Category**(*data*, *client*)

Bases: Model

Wrapper for the categories endpoint

DOCUMENTATION: str = 'https://adobe-commerce.redoc.ly/2.3.7-admin/tag/categories'

Link to the Official Magento 2 API documentation for the endpoint wrapped by the Model

IDENTIFIER: str = 'id'

The API response field that the endpoint's uid comes from

__init__(*data*, *client*)

Initialize a Category object using an API response from the categories endpoint

Parameters
data (dict) – raw API response

property excluded_keys

API response keys that shouldn't be set as object attributes by set_attrs()

Returns
list of API response keys that shouldn't be set as attributes

property custom_attributes: Dict[str, str]

property subcategories: List[Category]

The child categories, returned as a list of Category objects

Note: Only the direct child categories are returned. For a list of all descendants, use all_subcategories

property subcategory_ids: List[int]

The category_ids of the subcategories

property subcategory_names: List[str]

The names of the category's subcategories

property all_subcategories: Optional[List[Category]]

Recursively retrieves all descendants of the category

property all_subcategory_ids: List[int]

The category_ids of all_subcategories

property products: List[Product]

The Product s in the category

Alias for get_products()

property product_ids: List[int]

The product_ids of the category's products

property skus: List[str]

The skus of the category's products

property all_products: List[Product]

The Product s in the category and in all_subcategories

Alias for get_products() with search_subcategories=True

property all_product_ids: Set[int]

The product_ids of the products in the category and in all_subcategories

property all_skus: Set[str]

The skus of the products in the category and in all_subcategories

get_products(*search_subcategories=False*)

Retrieves the category's products

Parameters
search_subcategories (bool) – if True, also retrieves products from all_subcategories

Return type
Optional[*Union*[Product, *List*[Product]]]

get_orders(*search_subcategories=False*)

Retrieve any Order that contains one of the category's products

Parameters
search_subcategories (bool) – if True, also searches for orders from all_subcategories

Return type
Optional[Order | *List*[Order]]

get_order_items(*search_subcategories=False*)

Retrieve any OrderItem that contains one of the category's products

Parameters
search_subcategories (bool) – if True, also searches for order items from all_subcategories

Return type
Optional[OrderItem | *List*[OrderItem]]

get_invoices(*search_subcategories=False*)

Retrieve any Invoice that contains one of the category's products

Parameters
search_subcategories (bool) – if True, also searches for invoices from all_subcategories

Return type
Optional[Invoice | *List*[Invoice]]

add_product(*product*, *position=None*)

Adds a product to the category.

Note: This method can also be used to update the position of a product that's already in the category.

Parameters

- **product** (Union[str, Product]) – the product sku or its corresponding Product object
- **position** (Optional[int]) – the product position value to use

Returns
success status

Return type
bool

remove_product(*product*)
Removes a product from the category.

Parameters
product (Union[str, Product]) – the product sku or its corresponding Product object

Returns
success status

Return type
bool

4.4 The order module

class magento.models.order.**Order**(*data*, *client*)
Bases: Model

Wrapper for the orders endpoint

DOCUMENTATION: str = 'https://adobe-commerce.redoc.ly/2.3.7-admin/tag/orders'
Link to the Official Magento 2 API documentation for the endpoint wrapped by the Model

IDENTIFIER: str = 'entity_id'
The API response field that the endpoint's uid comes from

__init__(*data*, *client*)
Initialize an Order object using an API response from the orders endpoint

Parameters
- **data** (dict) – API response from the orders endpoint
- **client** (Client) – an initialized Client object

property excluded_keys: List[str]
API response keys that shouldn't be set as object attributes by set_attrs()

Returns
list of API response keys that shouldn't be set as attributes

property id: int
Alias for entity_id

property number: str
Alias for increment_id

property items: List[OrderItem]

The ordered items, returned as a list of `OrderItem` objects

Note: When a configurable `Product` is ordered, the API returns data for both the configurable and simple product

- The `OrderItem` is initialized using the configurable product data, since the simple product data is incomplete
- The `product` and `product_id` will still match the simple product though

If both entries are needed, the unparsed response is in the `data` dict

---

property item_ids: List[int]

The `item_id` s of the ordered `items`

property products: List[Product]

The ordered `items`, returned as their corresponding `Product` objects

get_invoice()

Retrieve the `Invoice` of the Order

Return type
Invoice

property customer: Customer

property shipping_address: dict

Shipping details, from `extension_attributes.shipping_assignments`

property bill_to: dict

Condensed version of the `billing_address` dict

property bill_to_address: str

The billing address, parsed into a single string

property ship_to: dict

Condensed version of the `shipping_address` dict

property ship_to_address: str

The shipping address, parsed into a single string

property payment: dict

Payment data

property net_tax: float

Final tax amount, with refunds and cancellations taken into account

property net_total: float

Final Order value, with refunds and cancellations taken into account

property item_refunds: float

Total amount refunded for items; excludes shipping and adjustment refunds/fees

property total_qty_invoiced: int

Total number of units invoiced

property total_qty_shipped: int
Total number of units shipped

property total_qty_refunded: int
Total number of units refunded

property total_qty_canceled: int
Total number of units canceled

property total_qty_outstanding: int
Total number of units that haven't been shipped/fulfilled yet

property net_qty_ordered: int
Total number of units ordered, after accounting for refunds and cancellations

class magento.models.order.**OrderItem**(*item*, *client=None*, *order=None*)
Bases: Model

Wrapper for the order/items endpoint

DOCUMENTATION: str = 'https://adobe-commerce.redoc.ly/2.3.7-admin/tag/ordersitems'
Link to the Official Magento 2 API documentation for the endpoint wrapped by the Model

IDENTIFIER: str = 'item_id'
The API response field that the endpoint's uid comes from

__init__(*item*, *client=None*, *order=None*)
Initialize an OrderItem using an API response from the orders/items endpoint

Note: Initialization requires either a Client or Order object

Parameters
- **item** (dict) – API response from the orders/items endpoint
- **order** (Optional[Order]) – the Order that this is an item of
- **client** (Optional[Client]) – the Client to use (if not initializing with an Order)

Raises
ValueError – if both the order and client aren't provided

property excluded_keys: List[str]
API response keys that shouldn't be set as object attributes by set_attrs()

Returns
list of API response keys that shouldn't be set as attributes

property order: Order
The corresponding Order

property product: Product
The item's corresponding Product

Note: If the ordered item:

- Is a configurable product - the child simple product is returned
- Has custom options - the base product is returned

---

property product_id: int
Id of the corresponding simple `Product`

property extension_attributes: dict

property qty_outstanding: int
Number of units that haven't been shipped/fulfilled yet

property net_qty_ordered: int
Number of units ordered, after accounting for refunds and cancellations

property net_tax: float
Tax amount after accounting for refunds and cancellations

property net_total: float
Row total (incl. tax) after accounting for refunds and cancellations

property net_refund: float
Refund amount after accounting for tax and discount refunds

property total_canceled: float
Cancelled amount; note that partial cancellation is not possible

4.5 The `invoice` module

class magento.models.invoice.**Invoice**(*data*, *client*)
Bases: `Model`

Wrapper for the `invoices` endpoint

DOCUMENTATION: str = 'https://adobe-commerce.redoc.ly/2.3.7-admin/tag/invoices'
Link to the Official Magento 2 API documentation for the endpoint wrapped by the Model

IDENTIFIER: str = 'entity_id'
The API response field that the endpoint's `uid` comes from

__init__(*data*, *client*)
Initialize an Invoice object using an API response from the `invoices` endpoint

Parameters

- **data** (`dict`) – API response from the `invoices` endpoint
- **client** (`Client`) – an initialized `Client` object

property excluded_keys: List[str]
API response keys that shouldn't be set as object attributes by `set_attrs()`

Returns
list of API response keys that shouldn't be set as attributes

property id: int
Alias for `entity_id`

property number: str
Alias for `increment_id`

property order: Order
The corresponding `Order`

property customer: Customer
The corresponding `Customer`

property items: List[InvoiceItem]
The invoiced items, returned as a list of `InvoiceItem` objects

class magento.models.invoice.**InvoiceItem**(*item*, *invoice*)
Bases: `Model`

Wraps an item entry of an `Invoice`

DOCUMENTATION: str = 'https://adobe-commerce.redoc.ly/2.3.7-admin/tag/invoicesid'
Link to the Official Magento 2 API documentation for the endpoint wrapped by the Model

IDENTIFIER: str = 'entity_id'
The API response field that the endpoint's `uid` comes from

__init__(*item*, *invoice*)
Initialize an InvoiceItem of an `Invoice`

Parameters

- **item** (`dict`) – API response to use as source data
- **invoice** (`Invoice`) – the `Invoice` that this is an item of

data_endpoint(*scope=None*)
No data endpoint exists for invoice items

query_endpoint()
No search endpoint exists for invoice items

property excluded_keys: List[str]
API response keys that shouldn't be set as object attributes by `set_attrs()`

Returns
list of API response keys that shouldn't be set as attributes

property order: Order
The `Order` this item is from

property order_item: OrderItem
The item's corresponding `OrderItem`

property product: Product
The item's corresponding simple `Product`

property product_id: int
Id of the corresponding simple `Product`

4.6 The `customer` module

class magento.models.customer.**Customer**(*data*, *client*)
Bases: `Model`

Wrapper for the `customers` endpoint

DOCUMENTATION: str = 'https://adobe-commerce.redoc.ly/2.3.7-admin/tag/customerscustomerId'
Link to the Official Magento 2 API documentation for the endpoint wrapped by the Model

IDENTIFIER: str = 'id'
The API response field that the endpoint's `uid` comes from

__init__(*data*, *client*)
Initialize a Customer object using an API response from the `customers` endpoint

Parameters
- **data** (`dict`) – API response from the `customers` endpoint
- **client** (`Client`) – an initialized `Client` object

property excluded_keys: List[str]
API response keys that shouldn't be set as object attributes by `set_attrs()`

Returns
list of API response keys that shouldn't be set as attributes

property name: str
The customer's full name

property is_subscribed: bool

property default_billing: Dict
Default billing address details

property default_billing_address: str
The default billing address, parsed into a single string

property default_shipping: Dict
Default billing address details

property default_shipping_address: str
The default shipping address, parsed into a single string

get_orders()
Retrieves `Order`s made by the customer

Returns
orders made by the customer, as an individual or list of `Order` objects

Return type
Optional[*Union*[Order, *List*[Order]]]

get_invoices()

Retrieves Invoices for the customer

Returns
invoices for the customer, as an individual or list of Invoice objects

get_ordered_products(*exclude_cancelled=True*)

Retrieves Products that the customer has ordered

Parameters
exclude_cancelled (bool) – flag indicating if products from cancelled orders should be excluded

Returns
products that the customer has ordered, as an individual or list of Product objects

CHAPTER

FIVE

GET A MAGENTO 2 REST API TOKEN WITH MYMAGENTO

Let's generate a Magento 2 REST API token using the MyMagento REST API wrapper package.

5.1 Setting the Login Credentials

Use your Magento 2 login credentials to generate an `ACCESS_TOKEN`

```
domain = 'domain.com'
username ='username'
password = 'password'
```

If you're using a local installation of Magento, your domain should look like this:

```
domain = '127.0.0.1/path/to/magento'
```

5.2 Getting a `Client`

Now that that's set that up, let's start using the API.

MyMagento uses the `Client` class to handle all interactions with the API

```
import magento

api = magento.get_api(domain=domain, username=username, password=password, local=True)
```

```
2023-02-15 01:09:05 INFO   |[ MyMagento | 127_adam ]|:  Authenticating adam on 127.0.0.1/
↪magento24...
2023-02-15 01:09:06 INFO   |[ MyMagento | 127_adam ]|:  Logged in to adam
```

5.3 Setting Environment Variables

To log in faster in the future, you can set the following environment variables:

```
import os

os.environ['MAGENTO_DOMAIN'] = domain
os.environ['MAGENTO_USERNAME']= username
os.environ['MAGENTO_PASSWORD']= password
```

The `Client` can now be initialized as follows

```
import magento

api = magento.get_api(local=True)
```

```
2023-02-15 01:09:28 INFO   |[ MyMagento | 127_adam ]|:  Authenticating adam on 127.0.0.1/
↪magento24...
2023-02-15 01:09:30 INFO   |[ MyMagento | 127_adam ]|:  Logged in to adam
```

CHAPTER

SIX

ADD DISCOUNT ON EACH PRODUCT BASED ON PRODUCT PRICE

I saw this question on Magento StackExchange:

Question

I have 100 products in my store and each product has different price. I want to add discount on each product based on specific price. For example, If a product is added into the cart and it has 100usd price then i want to apply 10% discount on it and if a product is added into the cart and it has 110usd price then i want to apply 11% discount on it and so on. I hope you understand what I want to achieve. in simple words, discount on each product based on product price. Thanks

6.1 Solution Using MyMagento

First, you'll want to *Get a Magento 2 REST API Token With MyMagento*

```
import magento

>>> api = magento.get_api()
```

Let's say we have the skus of the 100 products in an array.

We can use a `ProductSearch` retrieve these products as `Product` objects using `by_skulist()`

```
>>> skus = [f"test_sku{n}" for n in range(1, 101)]
>>> products = api.products.by_skulist(skus)
```

To retrieve the `Product` objects using a field other than `sku`, like `product_id`, we can use `by_list()`:

```
>>> product_ids = list(range(1,101))
>>> products = api.products.by_list(
...     field="entity_id",   # To search by product_id
...     values=product_ids
... )
```

Once we have our list of `Product` objects, we can calculate the discount based on their price, then update the `special_price` (discount price) using the `Product.update_special_price()` method

```
>>> for product in products:
...     if product.price < 100:
...         continue
```

(continues on next page)

(continued from previous page)

```
...
...     discount = product.price / 1000
...     price = product.price * (1 - discount)
...     product.update_special_price(round(price, 2))
```

We loop through our list of products and

1. Skip the products if the `price` is not $100 or more
2. Calculate the discount percentage by dividing the `price` by 1000
3. Calculate the new, discounted product price by multiplying the current `price` by `1 - discount`
4. Use the new price we calculated to update the `special_price` of the product

CHAPTER

SEVEN

CHANGELOG

7.1 v2.1.0

- Added `get_api()` to login using credentials stored in environment variables
  - The environment variables `MAGENTO_USERNAME`, `MAGENTO_PASSWORD`, `MAGENTO_DOMAIN` will be used if the `domain`, `username` or `password` kwargs are missing

```
import magento

>>> magento.get_api()

2023-02-08 03:34:20 INFO    |[ MyMagento | 127_user ]|:  Authenticating user on 127.0.0.1/
↪path/to/magento
2023-02-08 03:34:23 INFO    |[ MyMagento | 127_user ]|:  Logged in to user
<magento.clients.Client object at 0x000001CA83E1A200>
```

...

- Added `local` kwarg to `Client` to support locally hosted Magento stores and test environments
  - By default, `local=False`

```
from magento import Client

>>> api = Client("127.0.0.1/path/to/magento", "username", "password", local=True)
```

...

- Add `since()` and `until()` method to `SearchQuery` classes, which search the `created_at` field
  - They can be chained together and also with `add_criteria()`

Example

```
# Retrieve orders from the first 7 days of 2023
>>> api.orders.since("2023-01-01").until("2023-01-07").execute()

[<Magento Order: #000000012 placed on 2023-01-02 05:19:55>, ]
```

Example

```
# Retrieve orders over $50 placed since 2022
>>> api.orders.add_criteria(
...     field="grand_total",
...     value="50",
...     condition="gteq"
... ).since("2022-01-01").execute()

[<Magento Order: #000000003 placed on 2022-12-21 08:09:33>, ...]
```

...

- Changed `add_criteria()` to auto-increment the filter group by default if no group is specified (ie. `AND` condition)

```
# Retrieving products that are over $10 AND in the category with id 15
#
# Before v2.1.0
>>> api.products.add_criteria('category_id','15').add_criteria('price','10','gteq', group=1)

# v2.1.0+
>>> api.products.add_criteria('category_id','15').add_criteria('price','10','gteq')
```

...

- Changed the `Client.BASE_URL` to not include `"www."` at the start (see #8)
- Added unit tests for `url_for()`
- Added Jupyter notebook examples

CHAPTER

EIGHT

INDICES AND TABLES

- genindex
- modindex
- *Full Table of Contents*

PYTHON MODULE INDEX

m

magento.clients, 9
magento.exceptions, 30
magento.models.category, 51
magento.models.customer, 58
magento.models.invoice, 56
magento.models.model, 37
magento.models.order, 53
magento.models.product, 47
magento.search, 16
magento.utils, 31

INDEX

Symbols

__init__() (*magento.clients.Client method*), 9
__init__() (*magento.clients.Store method*), 14
__init__() (*magento.exceptions.AuthenticationError method*), 31
__init__() (*magento.exceptions.MagentoError method*), 30
__init__() (*magento.models.category.Category method*), 51
__init__() (*magento.models.customer.Customer method*), 58
__init__() (*magento.models.invoice.Invoice method*), 56
__init__() (*magento.models.invoice.InvoiceItem method*), 57
__init__() (*magento.models.model.APIResponse method*), 41
__init__() (*magento.models.model.Model method*), 37
__init__() (*magento.models.order.Order method*), 53
__init__() (*magento.models.order.OrderItem method*), 55
__init__() (*magento.models.product.MediaEntry method*), 48
__init__() (*magento.models.product.Product method*), 42
__init__() (*magento.models.product.ProductAttribute method*), 50
__init__() (*magento.search.CategorySearch method*), 30
__init__() (*magento.search.CustomerSearch method*), 29
__init__() (*magento.search.InvoiceSearch method*), 24
__init__() (*magento.search.OrderItemSearch method*), 22
__init__() (*magento.search.OrderSearch method*), 20
__init__() (*magento.search.ProductAttributeSearch method*), 28
__init__() (*magento.search.ProductSearch method*), 27
__init__() (*magento.search.SearchQuery method*), 16
__init__() (*magento.utils.MagentoLogger method*), 33

A

ACCESS_TOKEN (*magento.clients.Client attribute*), 10
active (*magento.clients.Store property*), 14
add_categories() (*magento.models.product.Product method*), 43
add_criteria() (*magento.search.SearchQuery method*), 16
add_media_type() (*magento.models.product.MediaEntry method*), 48
add_product() (*magento.models.category.Category method*), 52
add_product_link() (*magento.models.product.Product method*), 44
add_request_logging() (*magento.utils.MagentoLogger static method*), 35
all_product_attributes (*magento.clients.Store property*), 14
all_product_ids (*magento.models.category.Category property*), 52
all_products (*magento.models.category.Category property*), 51
all_skus (*magento.models.category.Category property*), 52
all_subcategories (*magento.models.category.Category property*), 51
all_subcategory_ids (*magento.models.category.Category property*), 51
APIResponse (*class in magento.models.model*), 41
attributes (*magento.search.ProductSearch property*), 27
authenticate() (*magento.clients.Client method*), 13
AuthenticationError, 31

B

BASE_URL (*magento.clients.Client attribute*), 10
bill_to (*magento.models.order.Order property*), 54
bill_to_address (*magento.models.order.Order property*), 54
by_category() (*magento.search.InvoiceSearch method*), 26
by_category() (*magento.search.OrderItemSearch method*), 24
by_category() (*magento.search.OrderSearch method*), 21
by_category() (*magento.search.ProductSearch method*), 27
by_category_id() (*magento.search.InvoiceSearch method*), 25
by_category_id() (*magento.search.OrderItemSearch method*), 23
by_category_id() (*magento.search.OrderSearch method*), 21
by_category_id() (*magento.search.ProductSearch method*), 28
by_code() (*magento.search.ProductAttributeSearch method*), 28
by_customer() (*magento.search.InvoiceSearch method*), 26
by_customer() (*magento.search.OrderSearch method*), 22
by_customer_id() (*magento.search.InvoiceSearch method*), 26
by_customer_id() (*magento.search.OrderSearch method*), 22
by_customer_id() (*magento.search.ProductSearch method*), 28
by_first_name() (*magento.search.CustomerSearch method*), 29
by_id() (*magento.search.CustomerSearch method*), 29
by_id() (*magento.search.ProductSearch method*), 27
by_id() (*magento.search.SearchQuery method*), 18
by_invoice() (*magento.search.CustomerSearch method*), 29
by_last_name() (*magento.search.CustomerSearch method*), 29
by_list() (*magento.search.SearchQuery method*), 18
by_name() (*magento.search.CategorySearch method*), 30
by_number() (*magento.search.InvoiceSearch method*), 24
by_number() (*magento.search.OrderSearch method*), 20
by_order() (*magento.search.CustomerSearch method*), 29
by_order() (*magento.search.InvoiceSearch method*), 24
by_order_id() (*magento.search.InvoiceSearch method*), 25
by_order_number() (*magento.search.InvoiceSearch method*), 24
by_product() (*magento.search.CustomerSearch method*), 29
by_product() (*magento.search.InvoiceSearch method*), 25
by_product() (*magento.search.OrderItemSearch method*), 23
by_product() (*magento.search.OrderSearch method*), 20
by_product_id() (*magento.search.InvoiceSearch method*), 25
by_product_id() (*magento.search.OrderItemSearch method*), 23
by_product_id() (*magento.search.OrderSearch method*), 21
by_sku() (*magento.search.InvoiceSearch method*), 25
by_sku() (*magento.search.OrderItemSearch method*), 23
by_sku() (*magento.search.OrderSearch method*), 20
by_sku() (*magento.search.ProductSearch method*), 27
by_skulist() (*magento.search.InvoiceSearch method*), 26
by_skulist() (*magento.search.OrderItemSearch method*), 24
by_skulist() (*magento.search.OrderSearch method*), 21
by_skulist() (*magento.search.ProductSearch method*), 27

C

cached (*magento.models.model.Model property*), 40
categories (*magento.clients.Client property*), 12
categories (*magento.models.product.Product property*), 46
Category (*class in magento.models.category*), 51
CategorySearch (*class in magento.search*), 30
children (*magento.models.product.Product property*), 46
clear() (*magento.models.model.Model method*), 40
clear_file_handlers() (*magento.utils.LoggerUtils static method*), 32
clear_handlers() (*magento.utils.LoggerUtils static method*), 32
clear_magento_file_handlers() (*magento.utils.MagentoLogger static method*), 34
clear_magento_handlers() (*magento.utils.MagentoLogger static method*), 34
clear_magento_stdout_handlers() (*magento.utils.MagentoLogger static method*),

35
clear_stream_handlers() (*magento.utils.LoggerUtils static method*), 32
Client (*class in magento.clients*), 9
client (*magento.search.SearchQuery attribute*), 16
CLIENT_LOG_NAME (*magento.utils.MagentoLogger attribute*), 33
configs (*magento.clients.Store property*), 14
critical() (*magento.utils.MagentoLogger method*), 34
custom_attributes (*magento.models.category.Category property*), 51
Customer (*class in magento.models.customer*), 58
customer (*magento.models.invoice.Invoice property*), 57
customer (*magento.models.order.Order property*), 54
customers (*magento.clients.Client property*), 12
CustomerSearch (*class in magento.search*), 29

D

data_endpoint() (*magento.models.invoice.InvoiceItem method*), 57
data_endpoint() (*magento.models.model.APIResponse method*), 41
data_endpoint() (*magento.models.model.Model method*), 38
debug() (*magento.utils.MagentoLogger method*), 34
default_billing (*magento.models.customer.Customer property*), 58
default_billing_address (*magento.models.customer.Customer property*), 58
DEFAULT_MSG (*magento.exceptions.AuthenticationError attribute*), 31
DEFAULT_MSG (*magento.exceptions.MagentoError attribute*), 30
default_shipping (*magento.models.customer.Customer property*), 58
default_shipping_address (*magento.models.customer.Customer property*), 58
delete() (*magento.clients.Client method*), 12
delete() (*magento.models.product.Product method*), 46
delete_product_link() (*magento.models.product.Product method*), 45
description (*magento.models.product.Product property*), 47
disable() (*magento.models.product.MediaEntry method*), 48
DOCUMENTATION (*magento.models.category.Category attribute*), 51
DOCUMENTATION (*magento.models.customer.Customer attribute*), 58
DOCUMENTATION (*magento.models.invoice.Invoice attribute*), 56
DOCUMENTATION (*magento.models.invoice.InvoiceItem attribute*), 57
DOCUMENTATION (*magento.models.model.Model attribute*), 37
DOCUMENTATION (*magento.models.order.Order attribute*), 53
DOCUMENTATION (*magento.models.order.OrderItem attribute*), 55
DOCUMENTATION (*magento.models.product.MediaEntry attribute*), 47
DOCUMENTATION (*magento.models.product.Product attribute*), 42
DOCUMENTATION (*magento.models.product.ProductAttribute attribute*), 50
domain (*magento.clients.Client attribute*), 10
download() (*magento.models.product.MediaEntry method*), 48

E

enable() (*magento.models.product.MediaEntry method*), 48
encode() (*magento.models.model.Model static method*), 40
encoded_sku (*magento.models.product.Product property*), 47
endpoint (*magento.search.SearchQuery attribute*), 16
error() (*magento.utils.MagentoLogger method*), 34
excluded_keys (*magento.models.category.Category property*), 51
excluded_keys (*magento.models.customer.Customer property*), 58
excluded_keys (*magento.models.invoice.Invoice property*), 56
excluded_keys (*magento.models.invoice.InvoiceItem property*), 57
excluded_keys (*magento.models.model.APIResponse property*), 41
excluded_keys (*magento.models.model.Model property*), 38
excluded_keys (*magento.models.order.Order property*), 53
excluded_keys (*magento.models.order.OrderItem property*), 55
excluded_keys (*magento.models.product.MediaEntry property*), 48

excluded_keys (*magento.models.product.Product property*), 42
excluded_keys (*magento.models.product.ProductAttribute property*), 50
execute() (*magento.search.SearchQuery method*), 18
extension_attributes (*magento.models.order.OrderItem property*), 56

F

fields (*magento.search.SearchQuery attribute*), 16
file_handlers (*magento.utils.MagentoLogger property*), 34
filter_website_attrs() (*magento.clients.Store method*), 15
format_msg() (*magento.utils.MagentoLogger method*), 34
FORMATTER (*magento.utils.MagentoLogger attribute*), 33
from_dict() (*magento.clients.Client class method*), 11
from_items() (*magento.search.OrderSearch method*), 22
from_json() (*magento.clients.Client class method*), 11
from_order_items() (*magento.search.InvoiceSearch method*), 26

G

get() (*magento.clients.Client method*), 12
get_agent() (*in module magento.utils*), 32
get_agents() (*in module magento.utils*), 31
get_all() (*magento.search.CategorySearch method*), 30
get_all() (*magento.search.ProductAttributeSearch method*), 28
get_all() (*magento.search.SearchQuery method*), 19
get_api() (*in module magento*), 9
get_children() (*magento.models.product.Product method*), 46
get_customers() (*magento.models.product.Product method*), 46
get_file_handlers() (*magento.utils.LoggerUtils static method*), 32
get_handler_by_log_file() (*magento.utils.LoggerUtils static method*), 32
get_handler_names() (*magento.utils.LoggerUtils static method*), 32
get_invoice() (*magento.models.order.Order method*), 54
get_invoices() (*magento.models.category.Category method*), 52
get_invoices() (*magento.models.customer.Customer method*), 59
get_invoices() (*magento.models.product.Product method*), 45
get_log_files() (*magento.utils.LoggerUtils static method*), 32
get_logger() (*magento.clients.Client method*), 13
get_magento_handlers() (*magento.utils.MagentoLogger static method*), 34
get_media_by_id() (*magento.models.product.Product method*), 47
get_order_items() (*magento.models.category.Category method*), 52
get_order_items() (*magento.models.product.Product method*), 45
get_ordered_products() (*magento.models.customer.Customer method*), 59
get_orders() (*magento.models.category.Category method*), 52
get_orders() (*magento.models.customer.Customer method*), 58
get_orders() (*magento.models.product.Product method*), 45
get_package_file_handler() (*in module magento.utils*), 35
get_package_handler() (*magento.utils.MagentoLogger static method*), 35
get_product_links() (*magento.models.product.Product method*), 46
get_products() (*magento.models.category.Category method*), 52
get_root() (*magento.search.CategorySearch method*), 30
get_scope_name() (*magento.models.model.Model method*), 40
get_stock() (*magento.search.ProductSearch method*), 28
get_stream_handlers() (*magento.utils.LoggerUtils static method*), 32
get_types() (*magento.search.ProductAttributeSearch method*), 29
global_product_attributes (*magento.clients.Store property*), 15

H

handler_map (*magento.utils.MagentoLogger property*), 34
HANDLER_NAME (*magento.utils.MagentoLogger attribute*), 33
handler_names (*magento.utils.MagentoLogger property*), 34

handlers (*magento.utils.MagentoLogger property*), 34
headers (*magento.clients.Client property*), 13

I

id (*magento.models.invoice.Invoice property*), 56
id (*magento.models.order.Order property*), 53
IDENTIFIER (*magento.models.category.Category attribute*), 51
IDENTIFIER (*magento.models.customer.Customer attribute*), 58
IDENTIFIER (*magento.models.invoice.Invoice attribute*), 56
IDENTIFIER (*magento.models.invoice.InvoiceItem attribute*), 57
IDENTIFIER (*magento.models.model.APIResponse attribute*), 41
IDENTIFIER (*magento.models.model.Model attribute*), 37
IDENTIFIER (*magento.models.order.Order attribute*), 53
IDENTIFIER (*magento.models.order.OrderItem attribute*), 55
IDENTIFIER (*magento.models.product.MediaEntry attribute*), 47
IDENTIFIER (*magento.models.product.Product attribute*), 42
IDENTIFIER (*magento.models.product.ProductAttribute attribute*), 50
info() (*magento.utils.MagentoLogger method*), 34
Invoice (*class in magento.models.invoice*), 56
InvoiceItem (*class in magento.models.invoice*), 57
invoices (*magento.clients.Client property*), 12
InvoiceSearch (*class in magento.search*), 24
is_enabled (*magento.models.product.MediaEntry property*), 48
is_single_store (*magento.clients.Store property*), 14
is_subscribed (*magento.models.customer.Customer property*), 58
is_thumbnail (*magento.models.product.MediaEntry property*), 48
item_ids (*magento.models.order.Order property*), 54
item_refunds (*magento.models.order.Order property*), 54
items (*magento.models.invoice.Invoice property*), 57
items (*magento.models.order.Order property*), 53

L

last_group (*magento.search.SearchQuery property*), 20
link (*magento.models.product.MediaEntry property*), 48
link (*magento.models.product.Product property*), 46
load() (*magento.clients.Client class method*), 11
log_files (*magento.utils.MagentoLogger property*), 34
LOG_MESSAGE (*magento.utils.MagentoLogger attribute*), 33
log_path (*magento.utils.MagentoLogger property*), 34
logger (*magento.clients.Client attribute*), 10
LoggerUtils (*class in magento.utils*), 32

M

magento.clients
    module, 9
magento.exceptions
    module, 30
magento.models.category
    module, 51
magento.models.customer
    module, 58
magento.models.invoice
    module, 56
magento.models.model
    module, 37
magento.models.order
    module, 53
magento.models.product
    module, 47
magento.search
    module, 16
magento.utils
    module, 31
MagentoError, 30
MagentoLogger (*class in magento.utils*), 33
map_handlers_by_name() (*magento.utils.LoggerUtils static method*), 33
media_gallery_entries (*magento.models.product.Product property*), 47
MEDIA_TYPES (*magento.models.product.MediaEntry attribute*), 47
MediaEntry (*class in magento.models.product*), 47
Model (*class in magento.models.model*), 37
Model (*magento.search.SearchQuery attribute*), 16
module
    magento.clients, 9
    magento.exceptions, 30
    magento.models.category, 51
    magento.models.customer, 58
    magento.models.invoice, 56
    magento.models.model, 37
    magento.models.order, 53
    magento.models.product, 47
    magento.search, 16
    magento.utils, 31

N

name (*magento.models.customer.Customer property*), 58
net_qty_ordered (*magento.models.order.Order property*), 55
net_qty_ordered (*magento.models.order.OrderItem property*), 56
net_refund (*magento.models.order.OrderItem property*), 56
net_tax (*magento.models.order.Order property*), 54
net_tax (*magento.models.order.OrderItem property*), 56
net_total (*magento.models.order.Order property*), 54
net_total (*magento.models.order.OrderItem property*), 56
new() (*magento.clients.Client class method*), 10
number (*magento.models.invoice.Invoice property*), 57
number (*magento.models.order.Order property*), 53

O

option_skus (*magento.models.product.Product property*), 47
options (*magento.models.product.ProductAttribute property*), 50
Order (*class in magento.models.order*), 53
order (*magento.models.invoice.Invoice property*), 57
order (*magento.models.invoice.InvoiceItem property*), 57
order (*magento.models.order.OrderItem property*), 55
order_item (*magento.models.invoice.InvoiceItem property*), 57
order_items (*magento.clients.Client property*), 12
OrderItem (*class in magento.models.order*), 55
OrderItemSearch (*class in magento.search*), 22
orders (*magento.clients.Client property*), 12
OrderSearch (*class in magento.search*), 20
owns_handler() (*magento.utils.MagentoLogger static method*), 35

P

pack_attributes() (*magento.models.model.Model static method*), 40
PACKAGE_LOG_NAME (*magento.utils.MagentoLogger attribute*), 33
parse() (*magento.exceptions.MagentoError static method*), 31
parse() (*magento.models.model.Model method*), 38
parse() (*magento.search.OrderItemSearch method*), 22
parse() (*magento.search.SearchQuery method*), 20
parse_domain() (*in module magento.utils*), 31
payment (*magento.models.order.Order property*), 54
post() (*magento.clients.Client method*), 12
PREFIX (*magento.utils.MagentoLogger attribute*), 33
Product (*class in magento.models.product*), 41
product (*magento.models.invoice.InvoiceItem property*), 57
product (*magento.models.order.OrderItem property*), 55
product_attributes (*magento.clients.Client property*), 12
product_id (*magento.models.invoice.InvoiceItem property*), 57
product_id (*magento.models.order.OrderItem property*), 56
product_ids (*magento.models.category.Category property*), 51
ProductAttribute (*class in magento.models.product*), 50
ProductAttributeSearch (*class in magento.search*), 28
products (*magento.clients.Client property*), 12
products (*magento.models.category.Category property*), 51
products (*magento.models.order.Order property*), 54
ProductSearch (*class in magento.search*), 27
put() (*magento.clients.Client method*), 12

Q

qty_outstanding (*magento.models.order.OrderItem property*), 56
query (*magento.search.SearchQuery attribute*), 16
query_endpoint() (*magento.models.invoice.InvoiceItem method*), 57
query_endpoint() (*magento.models.model.Model method*), 38
query_endpoint() (*magento.models.product.MediaEntry method*), 48

R

refresh() (*magento.clients.Store method*), 15
refresh() (*magento.models.model.Model method*), 39
remove_categories() (*magento.models.product.Product method*), 43
remove_media_type() (*magento.models.product.MediaEntry method*), 49
remove_product() (*magento.models.category.Category method*), 53
request() (*magento.clients.Client method*), 13
reset() (*magento.search.SearchQuery method*), 20

restrict_fields() (*magento.search.SearchQuery method*), 17
result (*magento.search.OrderItemSearch property*), 22
result (*magento.search.SearchQuery property*), 19
result_count (*magento.search.SearchQuery property*), 20
result_type (*magento.search.SearchQuery property*), 20

S

scope (*magento.clients.Client attribute*), 10
search() (*magento.clients.Client method*), 11
SearchQuery (*class in magento.search*), 16
set_alt_text() (*magento.models.product.MediaEntry method*), 49
set_attrs() (*magento.models.model.Model method*), 38
set_media_types() (*magento.models.product.MediaEntry method*), 49
set_position() (*magento.models.product.MediaEntry method*), 49
setup_logger() (*magento.utils.MagentoLogger method*), 33
ship_to (*magento.models.order.Order property*), 54
ship_to_address (*magento.models.order.Order property*), 54
shipping_address (*magento.models.order.Order property*), 54
since() (*magento.search.SearchQuery method*), 19
skus (*magento.models.category.Category property*), 51
special_price (*magento.models.product.Product property*), 47
STATUS_DISABLED (*magento.models.product.Product attribute*), 42
STATUS_ENABLED (*magento.models.product.Product attribute*), 41
stock (*magento.models.product.Product property*), 47
stock_item (*magento.models.product.Product property*), 47
stock_item_id (*magento.models.product.Product property*), 47
Store (*class in magento.clients*), 14
store (*magento.clients.Client attribute*), 10
store_view_product_attributes (*magento.clients.Store property*), 14
stream_handlers (*magento.utils.MagentoLogger property*), 34
subcategories (*magento.models.category.Category property*), 51
subcategory_ids (*magento.models.category.Category property*), 51
subcategory_names (*magento.models.category.Category property*), 51

T

thumbnail (*magento.models.product.Product property*), 47
thumbnail_link (*magento.models.product.Product property*), 47
to_dict() (*magento.clients.Client method*), 14
to_json() (*magento.clients.Client method*), 14
to_pickle() (*magento.clients.Client method*), 14
token (*magento.clients.Client property*), 13
total_canceled (*magento.models.order.OrderItem property*), 56
total_qty_canceled (*magento.models.order.Order property*), 55
total_qty_invoiced (*magento.models.order.Order property*), 54
total_qty_outstanding (*magento.models.order.Order property*), 55
total_qty_refunded (*magento.models.order.Order property*), 55
total_qty_shipped (*magento.models.order.Order property*), 54

U

uid (*magento.models.model.APIResponse property*), 41
uid (*magento.models.model.Model property*), 38
unpack_attributes() (*magento.models.model.Model static method*), 39
until() (*magento.search.SearchQuery method*), 19
update() (*magento.models.product.MediaEntry method*), 50
update_attributes() (*magento.models.product.Product method*), 44
update_custom_attributes() (*magento.models.product.Product method*), 44
update_description() (*magento.models.product.Product method*), 43
update_metadata() (*magento.models.product.Product method*), 43
update_name() (*magento.models.product.Product method*), 43
update_price() (*magento.models.product.Product method*), 42
update_special_price() (*magento.models.product.Product method*),

42
update_status() (*magento.models.product.Product method*), 42
update_stock() (*magento.models.product.Product method*), 42
url_for() (*magento.clients.Client method*), 11
user_agent (*magento.clients.Client attribute*), 10
USER_CREDENTIALS (*magento.clients.Client attribute*), 10

V

validate() (*magento.clients.Client method*), 13
validate_result() (*magento.search.SearchQuery method*), 19
view_config() (*magento.clients.Client method*), 14
views (*magento.clients.Store property*), 14
VISIBILITY_BOTH (*magento.models.product.Product attribute*), 42
VISIBILITY_CATALOG (*magento.models.product.Product attribute*), 42
VISIBILITY_NOT_VISIBLE (*magento.models.product.Product attribute*), 42
VISIBILITY_SEARCH (*magento.models.product.Product attribute*), 42

W

warning() (*magento.utils.MagentoLogger method*), 34
website_attribute_codes (*magento.clients.Store property*), 15
website_product_attributes (*magento.clients.Store property*), 15